



CEMbox 400I / 750I

D	CEMbox 400I / 750I mit Lenkrollen mit Feststeller Ø 125 mm Maximale Zuladung 200 kg	Deutsch	2 - 3
GB	CEMbox 400I / 750I with swivel castors with brake Ø 125 mm Maximum load capacity 200 kg	English	2 - 3
F	CEMBOX 400 L / 750 L avec roulettes avec blocage Ø 125 mm Charge maximale 200 kg	Français	2 - 3



CEMbox 400I



Objekt Object Objet	Anzahl Quantity Nombre	Bauteil Nummer Part number Référence	Bezeichnung Designation Désignation
①	4	211.4429.011	Abstandhalter für Lenkrolle Spacer for castor Entretoise pour roulettes
②	8	900.3114.000.A2	Scheibe R 14 DIN 440 A2 Washer R 14 DIN 440 A2 Rondelle R14 DIN 440 A2
③	4	900.1512.034.ZN	Sechskantschraube für Lenkrolle M12x90 DIN 931 Hex bolt for castor M12x90 DIN 931 Boulon 6 pans pour roulette M12x90 DIN 931
④	4	900.1612.023.ZN	Sechskantschraube für Abstandhalter M12x35 DIN 933 Hex bolt for spacer M12x35 DIN 933 Boulon 6 pans pour entretoise M12x35 DIN933
⑤	8	900.2613.000.ZN	Scheibe A 13 DIN 125 verzinkt Washer A 13 DIN 125 galvanised Rondelle A13 DIN 125 zinguée
⑥	8	900.2012.000.ZN	Sechskantmutter M12 DIN 985 Hex nut M12 DIN 985 Boulon hexagonal m12 DIN 985
⑦	4	928.1025.320	Lenkrolle Vollgummi 125x37,5 Traglast = 100kg Swivel castor solid rubber 125x37.5 mm Load capacity = 100kg Roulette tournante en caoutchouc 125x37,5 mm Capacité de charge = 100 kg





